



KONICA MINOLTA



CONNECT_COMMUNICATE_CONTROL

bizhub 362 PRINTER_COPIER_SCANNER_FAX



HIGH-SPEED, LOW-COST MULTIFUNCTION PRODUCTIVITY. Moving information faster is the whole idea behind bizhub — and for fast-growing document demands, the bizhub® 362 increases your power to print, copy, scan, even fax. At speeds up to 36 ppm, with workhorse 150,000-page monthly duty cycle, you'll be more productive right from the start. The built-in Emperon® Print System gives you built-in Windows Vista® and Mac® functionality. Security features provide best-in-class protection to safeguard essential data and guard against unauthorized access. Sleek center-office styling looks good anywhere — and PageScope® software provides seamless network management for documents and devices. If your workload keeps rising, let the bizhub 362 help keep you ahead of the curve.



business_by design



- ▶ HIGH-SPEED 36 PPM OUTPUT IN HIGH-RESOLUTION B&W
- ▶ 150,000 PAGE-PER-MONTH MAXIMUM DUTY CYCLE
- ▶ SIMITRI® TONER FOR FINE DETAIL, MORE LEGIBLE TEXT
- ▶ SLEEK DARK CABINET DESIGN, SMALL FOOTPRINT
- ▶ EMPERON® PRINT SYSTEM WITH PS/PCL EMULATION
- ▶ WINDOWS VISTA FUNCTIONALITY WITH 32-BIT/64-BIT DRIVERS
- ▶ FLEXIBLE SCANNING TO EMAIL, FTP, SMB (DESKTOP)
- ▶ SCAN-TO-HDD ON OPTIONAL 40 GB HARD DISK DRIVE
- ▶ IP ADDRESS FAX, PC FAXING, INTERNET FAX
- ▶ ISO 15408 CERTIFICATION, ENHANCED SECURITY PROTECTION*
- ▶ OPTIONS INCLUDE ADF, AUTO FINISHING, BOOKLET-MAKING
- ▶ 3,650-SHEET MAXIMUM PAPER CAPACITY WITH OPTIONS
- ▶ SUPER G3 FAX OPTION, OPTIONAL DUAL-LINE SUPPORT

*Certification Pending



The essentials of imaging



bizhub 362

PRINTER_COPIER_SCANNER_FAX_

CONNECT_COMMUNICATE_CONTROL_

General Specifications:

TYPE:	Digital Printer/Copier/Scanner/Fax
IMAGING SYSTEM:	Simitri® Polymerized Toner
SCANNING SYSTEM:	CCD Line Sensor
PRINT/COPY SPEED:	36 ppm (letter) 8-1/2" x 11" portrait, 29 ppm (letter) 8-1/2" x 11" landscape, 23 ppm (legal) 8-1/2" x 14", 20 ppm (ledger) 11" x 17"
MONTHLY DUTY CYCLE:	150,000 pages
PRINT/COPY RESOLUTION:	True 600 x 600 dpi
HALFTONE REPRODUCTION:	256 gradations
MEMORY:	192 MB (32 MB for files, 170 pages) (standard), 40 GB (maximum) (optional)
WARM-UP TIME:	14 seconds (from Sub Power On), 24 seconds (from Main Power On)
FIRST COPY:	4.8 seconds or less
COPY QUANTITY:	1 – 999 copies (countdown, interrupt capability)
MAGNIFICATION:	Zoom range: 25 – 400%, 0.1% increments, Preset reduction: 93%, 79%, 73%, 65%, 50%, Preset enlargement: 121%, 129%, 155%, 200%
EXPOSURE MODES:	Auto, Text, Photo, Text/Photo, Manual
ORIGINAL SIZE:	Up to 11" x 17" maximum
PAPER SIZE:	5-1/2" X 8-1/2" to 11" x 17"
PAPER WEIGHT:	15 lb. to 24 lb. bond, Manual bypass: 24-1/4 lb. to 55-3/4 lb. bond; specialty paper (thick paper, OHP transparencies, postcards, envelopes, label sheets)
STANDARD PAPER SUPPLY:	500-sheet Universal Paper Drawers (2), 150-sheet Intelligent Bypass
OPTIONAL PAPER SUPPLY:	500-sheet Universal Paper Cabinet (1 paper drawer plus storage drawer), 1,000-sheet Universal Paper Cabinet (two 500-sheet drawers), 2,500-sheet Large Capacity Cabinet
MAXIMUM PAPER CAPACITY:	3,650 sheets (total, with options)
DOCUMENT FEEDER:	DF-620 Reversing Auto Document Feeder (optional), Capacity: 80 sheets, Speed: up to 70 scans per minute, Original size: up to 11" x 17", 1-sided, 2-sided originals, Mixed Original Detection
POWER REQUIREMENTS:	120 V, 60 Hz, 11.5 A
POWER CONSUMPTION:	1380 W (max.)
DIMENSIONS (W x D x H):	26-3/4" x 28" x 28-1/4"
WEIGHT:	163 lbs.
OPTIONS:	DF-620 Reversing Automatic Document Feeder, DK-506 Copy Desk, EK-502 Local Interface Kit (IEEE Parallel), EM-303 32 MB Expanded Memory, EM-304 64 MB Expanded Memory, EM-305 128 MB Expanded Memory, FK-503 Fax Kit, FS-530 Base Finisher, HD-504 40 GB Hard Disk Drive, JS-502 Job Separator Tray, ML-502 Fax Dual Line (requires FK-503), MT-502 Mailbin Kit, OC-510 Original Cover, OT-602 Output Tray, PC-108 Universal Paper Feed Cabinet (500 sheets, statement to ledger size, plus storage drawer), PC-206 Universal Paper Feed Cabinet (500 sheets x 2, statement to ledger size), PC-407 Large Capacity Cabinet (2,500 sheets, letter portrait), PU-501 Punch Unit, SC-504 HDD Encryption Kit, SD-507 Saddle Stitcher, SP-501 Stamp Unit (requires FK-503), Spare TX Marker Stamp 2 (requires FK-503)
PAGESCOPE APPLICATIONS:	Network & Device Management: PageScope HDD Backup Utility, PageScope Web Connection, PageScope Net Care Device Manager, PageScope Network Setup, PageScope EMS Plug-Ins, PageScope NDPS Gateway, PageScope Data Administrator, PageScope Driver Packaging Utility, bizhub vCare, User Tools: PageScope Box Operator, PageScope Print Status Notifier, PageScope Web Print Assistant
AVAILABLE PRINT/COPY FUNCTIONS:	Account Track (up to 1,000 accounts), APS/AMS, Auto Duplex, Stackless, Auto/Manual/Photo Exposure, Auto Tray Switching, Black-White Reverse, Book Copy, Book Erase, Booklet Function, Box Function (stores copy jobs, print jobs, fax data, print stored data, route scanned data), Combined Copy Setting (2-in-1, 4-in-1), Copy Job Reserve (queue) (5 jobs), Copy Programs (Mode Memory) (10 jobs), Cover Mode, Criss/Cross Sorting, Distribution Number and Stamping, Energy Save Mode, Erase (Edge/Frame), File Margin, Hole-Punching (2/3 hole), Horizontal/Vertical Zoom Ratios (X/Y magnification), Image Overlay, Image Repeat, Image Rotation, Interrupt Mode, Mixed Original Detection, OHP Interleave, Page Insertion, Proof Copy, Separate Scanning, Sleep Mode Recovery, Stapling (single, multi-position, center), Text, Photo, Text/Photo, Dot Matrix Modes, Zoom

Emperon Print System (standard):

TYPE:	Embedded
PROCESSOR:	300 MHz
MEMORY:	192 MB (standard)
NETWORK INTERFACE:	RJ45 (Ethernet 10-BaseT/100-BaseTX) + USB 1.1/2.0 Port (standard), Parallel (IEEE 1284 compatibility) (optional)
NETWORK PROTOCOLS:	TCP/IP, IPX/SPX, SMB, LPD, IPP1.1, Apple Talk (Ether Talk), LPR, Netware (4.x, 5, 6), NDPS, SMTP, POP3, LDAP, SSL, SNMP, HTTP 3.0
SCANNING FUNCTIONS:	Scan-to-Email, Scan-to-FTP, Scan-to-HDD (with optional HDD), Scan-to-SMB (Scan-to-Desktop), Network HDD TWAIN
PRINT DRIVERS:	PCL6 emulation: Windows NT 4.0 (SP6a), Windows 2000 (SP4 or later), Windows XP (SP2 or later), Windows Server 2003, Windows Server 2008, Windows Vista 32-bit, 64-bit PostScript 3 emulation: Windows NT 4.0 (SP6a), Windows 2000 (SP4 or later), Windows XP (SP2 or later), Windows Server 2003, Windows Server 2008, Windows Vista 32-bit, 64-bit Mac OS 9.2 (PPD file), Mac OS X 10.2, 10.3, 10.4 or 10.5

FK-503 Fax Option Specifications

COMMUNICATION LINE:	Public Switched Telephone Network (PSTN)
COMPATIBILITY:	G3, Super G3
DATA COMPRESSION:	MH, MR, MMR, JBIG
MODEM SPEED:	33.6 kbps (max; auto fallback)
TRANSMISSION SPEED:	Less than 3 seconds per page
SCANNING SPEED:	Up to 70 sheets per minute (with DF-620 Reversing Auto Document Feeder option)
FAX RESOLUTION:	200 x 100 dpi, 200 x 200 dpi, 400 x 400 dpi, Text Photo (200 x 200 dpi), Grayscale (200 x 200 dpi), Super Grayscale (400 x 400 dpi)
MEMORY:	32 MB
FAX TRANSMISSION/RECEPTION SIZE:	Up to 11" x 17"
DIALING:	540 one-touch dialing locations
BROADCAST:	300 destinations
OTHER FACSIMILE FUNCTIONS:	IP Address Faxing, IP Relay Fax, PC Faxing

KONICA MINOLTA
 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
 100 Williams Drive
 Ramsey, NJ 07446
www.kmbusiness.konicaminolta.us
www.kmbusiness.konicaminolta.us/solutions

© 2009 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Konica Minolta and The essentials of imaging are trademarks of KONICA MINOLTA HOLDINGS, INC. bizhub, Emperon, and PageScope are trademarks of KONICA MINOLTA BUSINESS TECHNOLOGIES, INC. Simitri is a registered trademark of KONICA MINOLTA BUSINESS SOLUTIONS. All other brands and product names are registered trademarks or trademarks of their respective owners.

Design and specifications are subject to change without notice. Some functions may require options, which may or may not be available at time of launch.